

EVOLUTION IP RMS IP

Range of emergency power supplies with batteries in a 19" 2U rack
Multi-Applications - IP Management

12 V DC □ 24 V DC □ 48 V DC □ 56 V DC



Remote communication over IP and on the front panel by Digital Display

The emergency power supplies of the EVOLUTION IP □ RMS IP range provide permanent and backup power for all installations.



Rack 2U - face avant
483 x 89 x 395 mm



Rack 2U - face arrière
483 x 89 x 395 mm

Main functions

- ~ Controls and reports operating status over IP
- ~ Monitors battery presence
- ~ Protects the battery at end of discharge
- ~ Display of status on the front panel.

Benefits of the RMS IP range

- ~ Five fuse-protected load outlets
- ~ All connectors are pluggable
- ~ Built-in lightning protection
- ~ Fully-protected product, with rear connectors.

Ratings available

	300 W	600 W
12 V	8 to 16 A Util	16 to 32 A Util
24 V	4 to 10 A Util	10 to 16 A Util
48 V	2 to 4 A Util	4 to 10 A Util
56 V (continuous voltage output)	2 to 4 A Util	-

EVOLUTION IP & RMS IP is available in 2U Rack Enclosures.

Find all our references on our website www.slat.com and our Pricelist.



Multi-applications



Performance and reliability



Eco-design



Easy to install